

NEW!

Compactness and
performance combined with
maximum sustainability



SUSTAINABLE THINKING!
Minimal power consumption
No compressed air



ESPERA NOVA ES-E

The Compact Automatic Weighing & Labeling System –
digital, modular, sustainable

The compact, fully automatic weighing & labeling system ES-E enables maximum modularity combined with performance up to 80 packs/min.

For all applications in fresh food industry.



Think4Industry

The smart machine software for an easy, intuitive and predictive machine operation.

Terminal	15.6" Full glass color touch-screen
Machine software	Think4Industry
Weighing technology	1.5 kg, 3 kg / 0.5 g, 1 g
	3 kg, 6 kg / 1 g, 2 g
	6 kg, 15 kg / 2 g, 5 g
	80 packs/min.
Throughput	80 packs/min.
Label roll outer diameter	300 mm, inside/outside winded
Label roll core diameter	76 mm
Printing resolution	300 dpi
Printing speed	300 mm/s
Printing width	104 mm
Label size – maximum top (L x W) bottom (L x W)	150 x 110 mm
	150 x 110 mm
Label size – minimum top (L x W) bottom (L x W)	37 x 37 mm
	45 x 37 mm
TTF	Optional
Temperature range	0 °C to +40 °C
Power supply	180 V – 255 V, 50/60 Hz
IP-protection class scales	IPX 5
Label application technology	Electronially-controlled linear applicator
Automation	Optional: printer square adjustment, label rotation, product centering

Package mesures with 430 mm weighing belt	Package width	Max. 300 mm (with product centering) Max. 380 mm (without product centering) Min. 40 mm
	Package length	Max. 365 mm (dynamic) Max. 430 mm (start-stop) Min. 65 mm
	Package height	160 mm
Package mesures with 650 mm weighing belt	Package width	Max. 300 mm (with product centering) Max. 380 mm (without product centering) Min. 40 mm
	Package length	Max. 550 mm (dynamic) Max. 650 mm (start-stop) Min. 65 mm
	Package height	160 mm

ONE STEP AHEAD.

ESPERA-WERKE GMBH

Moltkestraße 17 - 33
47058 Duisburg
Germany

Telephone: +49 203 30 54 - 0

Fax: +49 203 30 54 - 275

E-Mail: info@espera.com

www.espera.com